XBO 6500 W/DHP IX OFR

XBO DHP for digital cinema projection | Xenonové světelné zdroje s krátkým obloukem

Druh použití

- Cinema projection

Vlastnosti produktu

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



© 2024, OSRAM GmbH. Všechna práva vyhrazena.

Technické údaje

Parametry

Jmenovitý proud	165 A
Jmenovitý výkon	650000 W
Rozsah řídícího proudu	133...173 A
Jmenovité napětí	390 V

Rozměry & váha

Průměr	785 mm
Délka	4360 mm
Délka s paticí bez konektorů	393,00 mm
Délka kabelu/drátu, vstup	155 mm
Vzdálenost světelného středu	170,5 mm [1)]
Mezera mezi elektrodami zastudena	8.1 mm
Váha výrobku	100000 g
Dálka vodiče	1550

[1)] Vzdálenost mezi okrajem patice a okrajem elektrody (za studena)

Teploty a provozní podmínky

Max. dovolená teplota v místě stisku	230 °C

Životnost

Střední doba života	1000 h
Service Warranty Lifetime	1200 h

Další údaje o produktu

Anoda (základní označení)	SFa30-7.9
Katoda (základní označení)	SFaX30-14

Vlastnosti

Chlazení	Nucený
Provozní poloha hořáku	h90 [1)]

[1)] Pro svislou provozní polohu: anoda (+) nahoře

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	07-07-2023
Primary Article Identifier	4062172363792

© 2024, OSRAM GmbH. Všechna práva vyhrazena.

Declaration No. in SCIP database	In work

© 2024, OSRAM GmbH. Všechna práva vyhrazena.

Bezpečnostní pokyny

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4062172363792	XBO 6500 W/DHP IX OFR	Shipping carton box 1	590 mm x 234 mm x 234 mm	32.31 dm^3	2149.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo vice samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

Vyloučení odpovědnosti

Změny bez předchozího upozornění vyhrazeny. Chyby a opomenutí vyhrazeny. Vždy se ujistěte, že používáte nejnovější vydání.

© 2024, OSRAM GmbH. Všechna práva vyhrazena.