

XBO 4000W/HPN XL OFR

XBO HPN for digital cinema projection | Xenonové světelné zdroje s krátkým obloukem



Druh použití

- Cinema projection

Vlastnosti produktu

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



Technické údaje

Parametry

Jmenovitý proud	122 A
Jmenovitý výkon	400000 W
Rozsah řídicího proudu	92...132 A
Jmenovité napětí	330 V

Rozměry & váha

Průměr	6000 mm
Délka	3450 mm
Délka s paticí bez konektorů	308,00 mm
Vzdálenost světelného středu	144,0 mm ¹⁾
Délka kabelu/drátu, vstup	235 mm
Mezera mezi elektrodami zastudena	6.1 mm
Váha výrobku	66400 g
Dálka vodiče	1950

¹⁾ Vzdálenost mezi okrajem patice a okrajem elektrody (za studena)

Teploty a provozní podmínky

Max. dovolená teplota v místě stisku	230 °C
--------------------------------------	--------

Životnost

Service Warranty Lifetime	2100 h
---------------------------	--------

Další údaje o produktu

Anoda (základní označení)	SFaX27-9.5
Katoda (základní označení)	SFa27-20

Vlastnosti

Chlazení	Nucený
Provozní poloha hořáku	s15/p15 ¹⁾

¹⁾ Pro svislou provozní polohu: anoda (+) nahoře

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-03-2024
Primary Article Identifier	4062172225489
Declaration No. in SCIP database	In work

Technický list výrobku

Bezpečnostní pokyny

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4062172225489	XBO 4000W/HPN XL OFR	Shipping carton box 1	500 mm x 204 mm x 204 mm	20.81 dm ³	1460.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

Vyloučení odpovědnosti

Změny bez předchozího upozornění vyhrazeny. Chyby a opomenutí vyhrazeny. Vždy se ujistěte, že používáte nejnovější vydání.