BX -DS-MP

BackLED DS Plus mounting profile | – Montážní profily



Vlastnosti produktu

- Celková délka: 2.000 mm
- Integrovaná montážní mřížka 50 mm pro jednoduché nastavení polohy LED modulů
- Možnost integrovaného upevnění pro kabely

Výhody produktu

- Možnost snadného zkrácení na libovolnou délku
- Rychlá a snadná montáž profilu pomocí závitořezných šroubů nebo slepých nýtů
- Rychlé a jednoduché nasazovací upevnění LED modulů, bez potřeby nástrojů
- Odolný hliníkový profil


Druh použití

- Světelné nápisy a světelná reklama
- Podsvícení oboustranných světelných boxů a stožárů
- Trvalé venkovní použití v uzavřených světelných boxech

© 2024, Inventronics GmbH. Všechna práva vyhrazena. Společnost Inventronics je držitelem licence na značku OSRAM. OSRAM je ochranná známka společnosti ams OSRAM.

Technické údaje

Rozměry & váha



Váha výrobku	352,60 g
Délka	2000 mm
Šířka	13,0 mm
Výška	13,3 mm


Logistická data

Zkratka produktu	76169990990

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	09-08-2022
Primary Article Identifier	4008321880307
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

© 2024, Inventronics GmbH. Všechna práva vyhrazena. Společnost Inventronics je držitelem licence na značku OSRAM. OSRAM je ochranná známka společnosti ams OSRAM.



boxLED mounting profile insert module

Stažení dat

	Soubor
	CAD data 652644_CAD Daten DS-Mounting profile_IGS
	CAD data 652645_CAD Daten DS-Mounting profile_STEP
	CAD data 652646_CAD Daten End cap-LEFT_IGS
	CAD data 652647_CAD Daten End cap-LEFT_STEP
	CAD data 652648_CAD Daten End cap-RIGHT_IGS
	CAD data 652649_CAD Daten End cap-RIGHT_STEP
	CAD data PDF 652654_CAD Daten DS-Mounting profile_pdf
	CAD data PDF 652655_CAD Daten End cap-LEFT_pdf

© 2024, Inventronics GmbH. Všechna práva vyhrazena. Společnost Inventronics je držitelem licence na značku OSRAM. OSRAM je ochranná známka společnosti ams OSRAM.

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4008321880307	BX -DS-MP	Shipping carton box 24	2060 mm x 116 mm x 64 mm	15.29 dm^3	9097.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

Vyloučení odpovědnosti

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, Inventronics GmbH. Všechna práva vyhrazena. Společnost Inventronics je držitelem licence na značku OSRAM. OSRAM je ochranná známka společnosti ams OSRAM.