

LFD400S -G1-850-06

LINEARlight FLEX Diffuse Side | – LED moduly pro profesionální a průmyslové aplikace



Vlastnosti produktu

- Long operational length per single power feed up to 10 m

Výhody produktu

- IP68 protection with high performance silicone
- Reliable connection over long periods of time: IP67 connector with built-in protection against liquids penetrating through the wires into the LED strip

Druh použití

- Světelné nápisy a světelná reklama



Technické údaje

Parametry


Jmenovitý příkon na metr	7,2 W
--------------------------	-------

Fotometrické údaje

Světelný tok na metr	430 lm
Standardní odchylka sladění barev	≤3 sdc _m
Index podání barev Ra	≥80
Teplota chromatičnosti	5000 K ¹⁾

¹⁾ Nominal descriptive value

Rozměry & váha



Váha výrobku	1040,00 g
Délka	6000,0 mm
Šířka	14,1 mm
Výška	10,80 mm

Logistická data

Zkratka produktu	85395100000
------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	02-06-2023
Primary Article Identifier	4062172007658
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Technický list výrobku

Declaration No. in SCIP database	67e58a94-3b05-4b50-be0d-415a56898b6e
----------------------------------	--------------------------------------

Text pro technický lis

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Stažení dat

Soubor
 User instruction LINEARlight FLEX DIFFUSE
 User instruction LINEARlight FLEX DIFFUSE
 Product Datasheet LINEARlight FLEX DIFFUSE Side_G2_Specification Sheet (EN)
 Product Datasheet LINEARlight FLEX DIFFUSE Side (EN)
 Brochures App Guide LINEARlight Flex Diffuse (EN)
 Brochures Light is freedom of design (EN)
 Declarations of conformity Flex Diffuse CE 3557934 221121
 Declarations of conformity 726048_Manufacturer Declaration_LINEARlight Flex Diffuse
 Eulumdat LFD400S-G1-850-06 LDT 28032022
 IES data LFD400S-G1-850-06 IES 28032022

Technický list výrobku

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4062172007658	LFD400S -G1-850-06	Shipping carton box 6	519 mm x 246 mm x 525 mm	67.03 dm ³	13358.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotku balení nebo násobky jednotek balení.

možné příslušenství

Popis výrobku	název příslušenství	kód příslušenství
LFD400S -G1-850-06	FX-LFDM -BEND-1000 KIT 3PCS	▶ 4062172192583

Vyloučení odpovědnosti

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.