# **OSRAM**

# BATTERYjumpstart 500



### Starts completely depleted batteries

New Boost function allows user to restart vehicles with depleted batteries



### **Powerful Lithium Battery**

Starts up to 3-liter petrol and 1.5-liter diesel vehicles



#### **USB Power Pack**

Charges phones and other devices via the built in USB port



## Powerful and safe jumpstarting for 12V vehicles with integrated USB charging and enhanced safety features

The OSRAM BATTERYjumpstart 500 can jump-start vehicles with engines up to 3L Petrol or 1.5L Diesel. It's suitable for most 12V cars, vans, SUVs, and LCVs. The boost function enables jump-starting of completely depleted batteries. The unique ergonomic smart clamp connection features longer cables for better accessibility in hard-to-reach areas. Safety features include reverse polarity protection, anti-spike protection, and short circuit protection, with audible and LED indicators. An integrated torch illuminates the work area, and LED indicators show the current battery level. The unit includes a USB-C port for recharging and a USB-A output for charging devices like tablets and phones.

## Product family datasheet

## Technical data

|                      | Product information                       |   |  | General Product<br>Information               |  |
|----------------------|---|---|--|--|--|
| Product description  | Recommended Petrol<br>Engine size (up to) | Recommended Diesel<br>Engine size (up to)   | Application (Category and Product specific)  | Global order reference                       |  |
| BATTERYjumpstart 500 | 3 l                                       | 1.5 l   | Lithium Starter  | OJS010                                       |  |
|                      | Electrical Data                           | Physical Attributes & Dimensions  |  |  |  |
| Product description  | Boost-Function (start batteries from 0V)  | Length  | Width  | Height                                       |  |
| BATTERYjumpstart 500 | Yes                                       | 254.0 mm  | 42.0 mm  | 94.0 mm                                      |  |
|                      |   | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) |  |  |  |
| Product description  | Candidate list substance 1                | CAS No. of substance  | Safe use instruction   | Declaration no. in SCIP database             |  |
| BATTERYjumpstart 500 | Lead                                      | 7439-92-1   | The identification of the Candidate List substance is sufficient to allow safe use of the article. | d36d90e1-ac19-<br>4777-a9de-<br>b52f99e724e1 |  |

## Product family datasheet

## Download Data

### File



Brochures

BATTERYjumpstart 500/1000 Lithium Starter

## **Application advice**

For more detailed application information and graphics please see product datasheet.

### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.