

TYREinflate 2130



Rapid digital inflator with quick set pressure and auto-stop

Extra large digital display makes monitoring inflation a breeze, whilst quick set pressure with auto-stop ensures accurate inflation every time



Designed for convenience

Features a wind-up power cable, onboard storage for the air hose and valve adaptors, and even a convenient post to store valve caps during inflation



Large, powerful LED light to illuminate workspace

For inflating in dark conditions, the large LED light is designed to illuminate the work area ahead without the need to reposition the inflator



Powerful, precise tyre inflation

Meet the flagship model in the next-generation range: the OSRAM TYREinflate 2130. Designed for those who demand OSRAM's topperformance, this advanced inflator features an extra-large digital pressure gauge with a progress bar for clarity and control. The intuitive quick-set dial allows you to input desired pressures in seconds, while the auto-inflation function ensures precise results every time. A convenient memory function recalls your last-used pressure setting for effortless repeat use.



Equipped with a 3.5 m wind-up 12V power cable, a 70 cm extra-long inflation hose, and a dedicated deflate button, the TYREinflate 2130 offers flexibility and control. A valve storage post and securely housed three valve adaptors add to its versatility, making it suitable for various inflation tasks. With a powerful motor that inflates a 13" tyre in just 2 minutes, the OSRAM TYREinflate 2130 delivers speed, power, and precision. ¹⁾²⁾

Product family datasheet

Technical data

Product description	General Product Information	Physical Attributes & Dimensions		
	Global order reference	Height	Width	Length
TYRE inflate 2130	OTI2130	152.0 mm	105.0 mm	220.0 mm
Product description	Operating Conditions	Additional product data	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
	Noise Level (dB)	Display Type	Fuse	Candidate list substance 1
TYRE inflate 2130	85 dB	Digital	15 A	Lead
Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database	
TYRE inflate 2130	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	a369e638-9ced-4549-a22b-1b08ffe69e69	

Download Data

File	
	User instruction TYREinflate 2130
	User instruction GPRS_Safety symbols instructions

Legal advice

- 1)Based on inflating a 13” tyre from flat to 2.4 BAR
- 2)Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.