Product family datasheet

LEDriving SL P21W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Cool White



Replaces conventional P21W lamps Easy upgrade to LED technology with

plug & play solutions



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21W

LEDriving SL P21W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

Product information						eneral Product formation		Electrical Data		
Product description		Application (Category and Product specific)		uct Global o (off- reference vs. ad)			Power Nominal voltag		voltage	
LEDriving SL \triangleq P21W	•	Mainly used for signal/ indicator applications		7506	DWF)	1.8 W	12 V		
						Photometric	Data	Physical A Dimensior	attributes &	
Product description	Nominal watta	Nominal wattage		Test voltage	Nominal lumi e flux		inous	Lamp base	2	
LEDriving SL \triangleq P21W	1 W		±25 %	13.5 V		160 lm		BA15s		
								Lifetime D	ata	
Product description	Length		Diameter			Diameter		Lifespan B3	Lifespan Tc	
LEDriving SL \triangleq P21W	52.5 mm		25.0 mm			25.0 mm		1500 hr	4000 hr	
	Capabilities					ormation EU Regulatior	n (EC) 190	7/2006		
Product description	Technology	Primary article identifier			Candidate list substance 1		CAS No. of substance 1		ce	
LEDriving SL \triangleq P21W	LED ¹⁾	406217 406217	062172348652 062172152181 062172401210 062172408318		Lead		7439-92-1			

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving SL \doteq P21W	The identification of	4b523b49-273b-
	the Candidate List	43fa-a900-
	substance is	dfef06fdea31
	sufficient to allow	e75f732e-151e-
	safe use of the	4392-9807-
	article.	f15711d460b4
		cbc40782-6f5e-4a73-
		ad3f-4f03b28c1891
		431a14a2-e6f5-451f-
		b379-4763b7bc7850

¹⁾ Light-emitting diode lamp

Product family datasheet

Download Data

File
User instruction GPRS_Safety symbols instructions
Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.