

BA -MP-M-CP-2

BackLED CP G4 – Mounting Profile | LED moduly pro světelnou reklamu a osvětlení pozadí – příslušenství



Vlastnosti produktu

- Overall length available in 1.5 m and 2 m
- Compatible with BackLED G4 family
- Suitable for BA-M-CP-G4 / BA-M-HO-CP-G4 / BA-S-CP-G4

Výhody produktu

- Možnost snadného zkrácení na libovolnou délku
- Rychlé a jednoduché nasazovací upevnění LED modulů, bez potřeby nástrojů
- Odolný hliníkový profil
- Rychlá a snadná montáž profilu pomocí závitořezných šroubů nebo slepých nýtů

Druh použití

- Suitable for BackLED S CP G4, BackLED M HO CP G4 and BackLED M Plus G4

Technické údaje

Rozměry & váha



Váha výrobku	13600 g
Délka	2000 mm
Šířka	163 mm
Výška	70 mm

Vlastnosti

Control interface	-
Detection angle (Light sensor)	-
Detection angle (PIR)	-

Logistická data

Zkratka produktu	76169990990
------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	13-02-2022
Primary Article Identifier	4062172168410
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Technický list výrobku

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4062172168410	BA -MP-M-CP-2	Shipping carton box 50	2015 mm x 150 mm x 80 mm	24.18 dm ³	8865.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

Vyloučení odpovědnosti

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.