

TF400RGB -G1-05

TEC FLEX Colormix IP00 | LED modules flexible, strips, colored



Vlastnosti produktu

- Pružný a stříhatelný pásek LED
- Up to 50,000 hrs lifetime @ tc max

Výhody produktu

- Jednotné změny barev
- Snadná montáž na mnoho hladkých povrchů pomocí samolepicí pásky na zadní straně

Druh použití

- Efektové osvětlení v architektuře



Technické údaje


Parametry

Jmenovité napětí	240 V
Proudové zatížení	stejnoseměrný proud (DC)
Jmenovitý příkon	4850 W
Rozsah vstupního napětí	23...25 V
Accidental reverse input voltage protection up to	25 V

Fotometrické údaje

Barva světla LED	RGB
Světelná účinnost	333 lm/W
Barva světla (označení)	červená/zelená/modrá
Světelný tok na metr	380 lm

Rozměry & váha



Délka	50000 mm
Váha výrobku	6500 g
Průřez kabelu, vstupní strana	0,5 mm ²
Šířka	800 mm
Výška	150 mm

Teploty a provozní podmínky

Provozní rozsah teplot	-25...80 °C
Skladujte při teplotách od... do	-30...85 °C

Další údaje o produktu

ID of contained light source [AGGR]	LS_SHZ_600468
-------------------------------------	---------------

Technický list výrobku

Certifikáty & standardy

Energy efficiency class of the contained light source	G
---	---

Logistická data

Zkratka produktu	85395100000
------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-07-2023
Primary Article Identifier	4062172154284
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	610b9928-cf09-4dc4-9282-a76db081ba4d

Výbava / příslušenství

- Zjednodušené zapojení pomocí systému CONNECTsystem jako příslušenství



TEC Flex RGB IP00

Stažení dat

Soubor	
	User instruction TEC Flex Tunable White, TEC Flex RGB

Technický list výrobku

	Product Datasheet TEC Flex RGB IP00 Product Datasheet, EN
	Brochures Light is strong - Discover the versatile and flexible lighting system OSRAM 24V TEC Flex (EN)
	Certificates TEC Flex RGB CE 4239858 210820
	Certificates TF(P)RGB ENEC 35-115144 140920
	Eulumdat Eulumdat TF400RGB-LDT
	IES data Eulumdat TF400RGB-IES

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. The contained light source is intended for use in applications requiring high-quality coloured light.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4062172154284	TF400RGB -G1-05	Shipping carton box 10	225 mm x 240 mm x 120 mm	6.48 dm ³	1304.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotku balení nebo násobky jednotek balení.

Technický list výrobku

možné příslušenství

Popis výrobku	název příslušenství	kód příslušenství
TF400RGB -G1-05	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
TF400RGB -G1-05	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
TF400RGB -G1-05	CONN-FLEX -4P-050 KIT 10PCS	▶ 4062172179744
TF400RGB -G1-05	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
TF400RGB -G1-05	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
TF400RGB -G1-05	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
TF400RGB -G1-05	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
TF400RGB -G1-05	FX -SC08-G2-CT4PJ	▶ 4052899464858

Vyloučení odpovědnosti

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.