

## LFP800S -G5-827-10 L1

LINEARlight FLEX Uniformity Protect | LED moduly pro profesionální a průmyslové aplikace



### Vlastnosti produktu

- 24 V LED strips flexible and cuttable, 50 mm cut unit, with superior optically graded silicone encapsulation
- Available variants: 800 lm/m 1200 lm/m 2000 lm/m / CRI Ra: 95+ 90+ and 80+
- Up to 60,000 h L90/B10 with SDT technology, tested acc. to IEC 62717 on real LED strips
- Stable light flux over length: active constant current regulators (ICs), PWM safe
- Embedded automatic quick protection against accidental miswiring up to 25 V
- Fully PWM dimmable from zero up to 2.5 kHz, audible noise free, suitable for quite places
- Excellent ESD protection of up to 8 kV in air or 4 kV in contact (acc. to IEC 61547)
- Designed, engineered and manufactured and tested in Italy (ISO9001, ISO 17025, ACCREDIA, VDE)
- Salt-mist atmosphere resistant (acc. to IEC 60068-2-52, highest severity)
- UV radiation resistant (acc. to ISO 4892-2) / Mixed flowing gas corrosion resistant (IEC 60068-2-60)

### Výhody produktu

- Color uniformity better than 2 SDCM on the entire LED strip and between strips
- Light stability over time typically 1 SDCM, tested acc. to IEC 62717 @ 6,000 h
- LED lifetime acc.to IES LM-80 and IES TM-21 standards, and also internal OSRAM LAB tests
- Reliable photometric parameters according to IES LM-79, EN13032-4 and CIE S 025
- Accurate description of the color rendition of the light source acc. to IES TM-30-15
- Excellent robustness: single reel manufacturing technology (no solder joints on strip)
- Vibration-resistant for stationary installations acc. to IEC60068-2-6 and IEC60068-2-64
- Flicker and stroboscopic effect-free acc. to IEC TR 61547-1 and IEC TR 63158
- Tested by accredited Product Qualification Lab. ISO9001, ISO 17025, ACCREDIA, VDE
- Snadná montáž na mnoho hladkých povrchů pomocí samolepicí pásky na zadní straně



Technické údaje

Parametry

|                                                   |                          |
|---------------------------------------------------|--------------------------|
| Jmenovité napětí                                  | 24,0 V                   |
| Proudové zatížení                                 | stejnoseměrný proud (DC) |
| Jmenovitý příkon na metr                          | 7,2 W                    |
| Jmenovitý příkon                                  | 72,00 W                  |
| Rozsah vstupního napětí                           | 23...25 V                |
| Accidental reverse input voltage protection up to | 25 V                     |

Fotometrické údaje

|                                   |          |
|-----------------------------------|----------|
| Barva světla LED                  | bílá     |
| Index podání barev Ra             | 80       |
| Světelný tok na metr              | 840 lm   |
| Celkový užitečný světelný tok     | 8400 lm  |
| Světelná účinnost                 | 117 lm/W |
| Standardní odchylka sladění barev | ≤3 sdc   |
| Barva světla (označení)           | 2700 K   |
| Teplota chromatičnosti            | 2700 K   |

Světelně-technické údaje

|                       |         |
|-----------------------|---------|
| LED pitch             | 7.14 mm |
| Vyzařovací úhel       | 120 °   |
| Doba startu           | 0,0 s   |
| Doba zahřívání (60 %) | 0,00 s  |

Informace o LED modulech

|                               |     |
|-------------------------------|-----|
| Počet čísel na metr           | 140 |
| Počet LED v nejmenší jednotce | 7   |

Rozměry & váha



|                               |                     |
|-------------------------------|---------------------|
| Délka                         | 10000,0 mm          |
| Délka nejmenší jednotky       | 50,0 mm             |
| Šířka                         | 11,1 mm             |
| Výška                         | 4,50 mm             |
| Dálka vodiče                  | 500,0               |
| Váha výrobku                  | 638,00 g            |
| Průřez kabelu, vstupní strana | 0,5 mm <sup>2</sup> |

Barvy & materiály

|                        |          |
|------------------------|----------|
| Výrobní materiál obalu | Silicone |
|------------------------|----------|

Teploty a provozní podmínky

|                                  |                            |
|----------------------------------|----------------------------|
| Provozní tepl. podle IEC 62717   | 30 °C                      |
| Provozní rozsah teplot           | -30...80 °C <sup>1)</sup>  |
| Rozsah okolní teploty            | -30...+50 °C <sup>2)</sup> |
| Skladujte při teplotách od... do | -40...85 °C                |

<sup>1)</sup> Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

<sup>2)</sup> Rated ambient temp. 25°C/Providing that temperature at Tc point is below max value during operation/Temperature ramping for environmental testing acc. to IEC 62717, 1K/min

Životnost

|                                     |         |
|-------------------------------------|---------|
| Měřená životnost                    | 60000 h |
| Jmenovitá životnost                 | 60000 h |
| Pokles sv. toku na konci prům. živ. | 0,70    |
| Počet spínacích cyklů               | 15000   |

Další údaje o produktu

|                                     |               |
|-------------------------------------|---------------|
| ID of contained light source [AGGR] | LS_TRV_285965 |
|-------------------------------------|---------------|

Vlastnosti

|                       |       |
|-----------------------|-------|
| Stmívatelnost         | Ano   |
| Lowest bending radius | 50 mm |
| Self-adhesive         | Ano   |
| With connection set   | Ne    |
| With end piece        | Ne    |

Certifikáty & standardy

|                                                       |                |
|-------------------------------------------------------|----------------|
| Spotřeba energie                                      | 80 kWh/1000h   |
| Standardy                                             | CE/UL/ENEC/EAC |
| Druh ochrany                                          | IP68/IP65      |
| Energy efficiency class of the contained light source | F              |

Logistická data

|                  |             |
|------------------|-------------|
| Zkratka produktu | 85395100000 |
|------------------|-------------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                                                                                    |
|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Date of Declaration                                                   | 16-06-2023                                                                                         |
| Primary Article Identifier                                            | 4062172303477                                                                                      |
| Candidate List Substance 1                                            | Lead                                                                                               |
| CAS No. of substance 1                                                | 7439-92-1                                                                                          |
| Safe Use Instruction                                                  | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database                                      | 4756443d-7028-4ae7-88e0-faa289b82224                                                               |

Stažení dat

| Soubor                                                                              |                                                                                            |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
|  | User instruction<br>LINEARlight FLEX Protect Uniformity LFP800S-G5 LFP1200S-G5 LFP2000S-G5 |
|  | Product Datasheet<br>LINEARlight FLEX Protect Uniformity L1 Specification Sheet (EN)       |
|  | Brochures<br>Light is freedom of design (EN)                                               |
|  | Certificates<br>LF(P)-Uniformity CB 181120                                                 |
|  | Certificates<br>VDE ENEC CERTIFICATE 40052516 160823                                       |

Technický list výrobku

|                                                                                   |                                     |
|-----------------------------------------------------------------------------------|-------------------------------------|
|  | Eulumdat<br>LFP800S-G5-827-10 C_ldt |
|  | IES data<br>LFP800S-G5-827-10 C_IES |

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistické údaje

| Kód výrobku   | Popis výrobku         | Jednotka balení<br>(kusy/jednotku) | Rozměry (délka x šířka x<br>výška) | Objem                 | Hrubá<br>hmotnost |
|---------------|-----------------------|------------------------------------|------------------------------------|-----------------------|-------------------|
| 4062172303477 | LFP800S -G5-827-10 L1 | Shipping carton box<br>8           | 365 mm x 286 mm x 366 mm           | 38.21 dm <sup>3</sup> | 9322.00 g         |

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

možné příslušenství

| Popis výrobku         | název příslušenství             | kód<br>příslušenství |
|-----------------------|---------------------------------|----------------------|
| LFP800S -G5-827-10 L1 | ENDCAP -IP67 KIT 10PCS          | ▶ 4062172176552      |
| LFP800S -G5-827-10 L1 | JUMPER -FLEX-IP67-2P KIT 5PCS   | ▶ 4062172176576      |
| LFP800S -G5-827-10 L1 | CONN-FLEX -IP67-2P KIT 5PCS     | ▶ 4062172176590      |
| LFP800S -G5-827-10 L1 | LTS-SLIMTRACK -2000 KIT 5 PCS   | ▶ 4062172207300      |
| LFP800S -G5-827-10 L1 | CONN-FLEX -IP67-2P-300 KIT 5PCS | ▶ 4062172230162      |

Technický list výrobku

|                       |                          |                 |
|-----------------------|--------------------------|-----------------|
| LFP800S -G5-827-10 L1 | FX-QMS-G1 -TU15H6W3-300  | ▶ 4052899448889 |
| LFP800S -G5-827-10 L1 | FX-QMS-G1 -TU16H12W3-300 | ▶ 4052899448988 |
| LFP800S -G5-827-10 L1 | FX-QMS-G1 -TU16H12-300   | ▶ 4052899448964 |

Vyloučení odpovědnosti

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.