

LF -4CONN Protect

RGB 4pin LINEARlight Flex IP67 Connector | Accessories for Flexible LED strips

Vlastnosti produktu

- Quick and easy installation
- Compatible with TEC Flex




Výhody produktu

- Jednoduchá instalace, není třeba použít žádné nástroje ani pájení (CONNECTsystem)
- Kratší doba montáže (CONNECTsystem)
- Možnost připojení na čelní části modulu nebo v dělicích bodech (CONNECTsystem)
- Plochý tvar (CONNECTsystem)

Technické údaje

Rozměry & váha



Délka	300 mm
Váha výrobku	2000 g
Průřez kabelu, vstupní strana	1,4 mm ²
Šířka	198 mm
Výška	134 mm

Další údaje o produktu

Doporučená náhrada EAN	4062172016452
Doporučená náhrada EAN	4008321977090

Logistická data

Zkratka produktu	85444290900
------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	26-04-2024
Primary Article Identifier	4062172016452
Declaration No. in SCIP database	In work

Stahování dat

Soubor	
	Brochures Light is freedom of design (EN)



Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4062172016452	LF -4CONN Protect	Shipping carton box 10	230 mm x 150 mm x 340 mm	11.73 dm ³	625.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

Vyloučení odpovědnosti

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.