

LEDDriving HLM EASY GEN 2 H4/H19



Ultra compact LED replacement for conventional H4/H19 high and low beam lamps

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation



Cool White color temperature

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system: no adapters and caps needed.

With its socket-based solution, the OSRAM LEDDriving HLM EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional H4/H19 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HLM EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for motorcycles with the respective halogen lamp types.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technický list řady výrobků

Technické údaje

Popis výrobku	Parametry			Fotometrické údaje	
	Příkon	Jmenovité napětí	Jmenovitý výkon	Světelný tok	Tolerance světelného toku
LEDDriving HL EASY GEN 2 ≙ H4/H19	16.5W/1 6.5 W	12 V	22 W	1850/1500 lm	±25 %

Popis výrobku	Physical Attributes & Dimensions	Životnost	Informace o životním prostředí a právních předpisech Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Průměr	Životnost Tc	Primární identifikátor článku	Číslo prohlášení v databázi SCIP
LEDDriving HL EASY GEN 2 ≙ H4/H19	21.5 mm	1000 hr	4062172420327	V procesu

Stažení dat

Soubor	
	User instruction GPRS_Pokyny k bezpečnostním symbolům
	Brochures LEDriving Retrofits - Exchange overview (EN)

Bezpečnostní pokyny

Application advice:

For more detailed application information and graphics please see product datasheet and user manual.

Pokyny k použití

Podrobnější informace k použití a grafiku najdete v technickém listu.

Vyloučení odpovědnosti

Změny bez předchozího upozornění vyhrazeny. Chyby a opomenutí vyhrazeny. Vždy se ujistěte, že používáte nejnovější vydání.