OSRAM

LEDinspect UTILITY1000

Inspectionlights





Multi-Functional Lamp

High flexibility and diverse adjustment possibilities. Up to 180° ratcheting bases and up to 360° rotating body.



1000 lm

2 light functions: Up to 1000lm-high Up to 400lmlow For individually adjustable light settings



Magnetic Base & Rotatable Hook Versatile mounting options



2-year-OSRAM guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

Light is versatile

Designed with versatility in mind, the UTILITY 1000 combines magnetic, 180° ratcheting base with a 360° rotating body. This means the inspectionlight can be used either freestanding or hands-free, positioned in any number of ways to ensure the work area is properly illuminated. With two light functions - high with up to 1000lm and low with up to 400lm - it produces a light output that can be matched to the task at hand.

This inspection light is ideal as a light for manual work, car repairs and everyday use. OSRAM also provides a 2-year guarantee on this product* Charging cable and mains



charger included.

Technical data

| | Product information Application (Category and Product specific) | | General Product Information Global order reference | | Electrical Data Nominal voltage | | Nominal wattage |
|---------------------|---|-------------------------------|---|--------------------------|------------------------------------|---------------------------------|--|
| Product description | | | | | | | |
| INSPECTION LAMP | LED inspection lights | | LEDIL407 | | 7.4 V | | 19 W |
| | Photometric [| Data | | | | Physic Dimen | al Attributes & sions |
| Product description | Light color LED | - | | inous Color temperature | | Height | |
| INSPECTION LAMP | White | White 1000 lm 6500 K | | (| 48.0 mm | | |
| | | | | | | | LED module information |
| Product description | Width | Width | | Length | | t | Number of LEDs per module |
| INSPECTION LAMP | 41.0 mm | | 500.0 mm | | 490.00 g | | 1 |
| | Colors & materials | | Lifetime Data | Additional product data | | | |
| Product description | Base color | Base color | | | | Number of included batteries | |
| INSPECTION LAMP | Black / Orang | e | 2 years | Yes | | 1 | |
| | | | Capabilities | Certificates & standards | | Logistical data | |
| Product description | Type of Batte | Type of Battery | | IK Class | | Watt hour per battery | |
| INSPECTION LAMP | Rechargeable | | LED | IK07 | | 9.62 | |
| | | - | latory Informat Art. 33 of EU Re | | (EC) 1907/2006 | (REACh) | |
| Product description | Candidate list substance 1 | Candidate list substance 1 | | CAS No. of substance | | uction | Declaration no. in SCIP database |
| INSPECTION LAMP | Lead | Lead | | 7439-92-1 | | tion of List llow | 12140b2a-ec70- 4b9c-9c15- 9b33a359d5fe |

Download Data

| | File |
|---|--|
| * | User instruction LEDinspect UTILITY 1000 LEDIL407 |
| 1 | User instruction GPRS_Safety symbols instructions |

Legal advice

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.