OSRAM

LEDinspect WEARABLE NECKLIGHT





Detachable Torches

High flexibility - can be placed around the neck, on the head, in the hand or on a magnetic surface



Up to 265 lm (high) & 130 lm (low)

Two light functions: Up to 265 lm (high) and up to 130 lm (low)



Approx. 1.5 hours charging time

With a charging time of only approx. 1.5 hours, this OSRAM light is quickly ready for use again



2-year OSRAM Guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

Light is versatile

This rechargeable neck light with two individually detachable torches from OSRAM is perfect for professional and private use. With two light functions up to 265lm (high), 130lm (low) and an adjustable 90 degree angle, this offers different setting options for a variety of tasks. The LEDinspect Wearable Neck Light is particularly impressive with its great flexibility - it can be used around the neck, on the head, in the hand or on a magnetic surface. The rechargeable battery allows up to 3 hours of operation at high power or up to 4.5 hours at low power and with a charging time of only about 1.5 hours, this OSRAM lamp is

Product family datasheet



also quickly ready for use again. A USB Micro B charging cable with two connections for the individual lamps to charge the lithium battery is included. In accordance with protection class IP54, this lamp has protection against the ingress of dust particles and against splashing water and has been tested for impact resistance in accordance with IK07. With a weight of only 115g and the flexible design, the product is easy to store and transport and is therefore ideal as a light for handicraft work, craft activities, car repairs and in everyday life. OSRAM also provides a 2-year guarantee*

*For precise conditions please refer to:
www.osram.com/am-guarantee

Product family datasheet

Technical data

	<u>[</u>		I		I			
	Product inform	Product information		General Product Information		Electrical Data		
Product description		Application (Category and Product specific)		Global order reference		ge	Nominal wattage	
INSPECTION LAMP	LED inspection	lights	LEDIL413		3.7 V		1 W	
	Photometric D	ata				Physica Dimens	l Attributes & ions	
Product description	Light color LED	Nomina flux	al luminous	Color to	emperature	Height		
INSPECTION LAMP	White	265 lm		6500 K		150 mn	n	
							LED module information	
Product description	Width		Length		Product weigh	t	Number of LEDs per module	
INSPECTION LAMP	25.0 mm		158.0 mm		115.00 g		1+1	
	Colors & mate	Colors & materials		Additional product data				
Product description	Base color		Guarantee	Number batteries		Type of E	Battery	
INSPECTION LAMP	Black / Orange		2 years	1		Recharge	eable	
	Capabilities	Certific standa		Logistic	cal data	Regulat Informa Informa accordi EU Reg	ition	
Product description	Technology	Technology IK Class		Watt h	our per battery	Candidate list substance 1		
INSPECTION LAMP	LED	IK07		2.96		Lead		

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
INSPECTION LAMP	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9b7cd37b-d0e8- 4a84-abf2- d10e9bfc7dfe

Product family datasheet

Download Data

File



User instruction
GPRS_Safety symbols instructions

Legal advice

Application advice: For more detailed application information and graphics please see product datasheet and the user instruction.* for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.