OSRAM

LEDriving HLM EASY T19



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



Superior brightness

Allowing a high compatibility and an easy installation.



LED replacement for conventional T19 high and low beam lamps

Reduced glaring thanks to an optimal light distribution



LED high and low beams lamps with plug & play system for motorcycles.

The OSRAM LEDriving HLM EASY represent an easy solution to upgrade conventional motorcycle headlights with cool white LED light – with a color temperature of 6,000 K, they provide a stylish and modern look as well as superior brightness. Equipped with the latest LED technology and a very compact design, these lamps allow high compatibility and an easy installation for a wide range of motorcycle models. The LEDriving HLM EASY lamps are 12V and AC/DC compatible and offer a long service life. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

LEDriving HLM EASY T19

5 W

Technical data

	Product information		General Product Information		Electrical Data		
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global order reference		Power input	Nominal volta	age
LEDriving HLM EASY T19	Mainly used for headlight applications	Off-road T19	7335DW	ESY	4.5 W / 5.5 W	13.5 V	
		Photometric Data		Physical Attributes & Dimensions			
Product description	Nominal wattage	Nominal lum flux	inous	Luminous flux tolerance	Diamete	er	Diamete r

	Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Lifespan B3	Lifespan Tc	Technology	Primary article identifier	Candidate list substance 1	
LEDriving HLM EASY T19	500 hr	1000 hr	LED	4062172345545 4062172399883	Lead	

600/500 lm

±15 %

18.4 mm

18.4 mm

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving HLM EASY T19	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	efa593e8-2c11-4e97- 9734-d514687a1b08 5ec6e727-7f8a- 4bc0-ac15- c8ce50c92a5f

Product family datasheet

Download Data

File



User instruction
GPRS_Safety symbols instructions

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.